



1019.00 EUR  
incl. 19% VAT, plus [shipping](#)

- VIA VX800 Chipset
- Support VIA Eden 1.6GHz processor
- Integrated Chrome9 HC3 DX9 IGP
- Integrated LVDS support 24-bit TFT LCD
- Support 1 x 32-bit PCI slot
- Support 2 x Serial ATA 2 Devices
- Windows Vista Ready
- Onboard Gigabit LAN
- Support DC FAN
- COM2 Support RS422/485
- VIA VT1708B HD Audio Codec with 6-Channel
- 170 x 170mm Mini-ITX Form Factor
- Support Daughter board Expansion
- Support Watch dog Technology

- |                     |                                                                              |
|---------------------|------------------------------------------------------------------------------|
| 1. CPU              | 1. Support VIA Eden 1.6GHz(90nm, FSB 800MHz,1.6GHz) processor                |
|                     | 2. Front Side Bus 800MHz                                                     |
| 1. Chipset          | 1. VIA VX800 Chipsets                                                        |
|                     | 2. VIA Chrome9 HC3 IGP, 128Bit 3D engines( Share System Memory:64/128/256MB) |
| 1. Memory           | 1. 1 * 240-pin DIMM Sockets for un-buffered DDR2 667MHz SDRAM up to 2GB      |
| 1. Expansion Slots  | 1. 1 * 32-bit PCI slots                                                      |
| 1. Power Management | 1. ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature                    |

- 
- |                     |                                                                |
|---------------------|----------------------------------------------------------------|
| 1. Storage          | 1. 2 * Serial ATA2 3Gb/s connectors with RAID 0,1 functions    |
|                     | 2. 1 * Ultra DMA 133/100/66 IDE connector                      |
| 1. Audio            | 1. VIA VT1708B HD Audio Codec with 6-Channel                   |
| 1. Ethernet LAN     | 1. 1 * RTL8111C 10 / 100 / 1000 PCI LAN                        |
| 1. USB              | 1. Embedded 6 * USB 2.0/1.1                                    |
| 1. LVDS             | 1. Onboard 24-bit dual channel LVDS connector                  |
| 1. Rear Panel I / O | 1. 2 * USB 2.0/1.1 ports                                       |
|                     | 2. 1 * PS/2 connector for Keyboard and Mouse                   |
|                     | 3. 1 * RJ-45 ports                                             |
|                     | 4. 3 * Audio I/O ports ( Line-in, mic and line-out )           |
|                     | 5. 1 * VGA port                                                |
|                     | 6. 1 * DB-9 RS232 COM port                                     |
| 1. Internal I / O   | 1. 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports                 |
|                     | 2. 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors |
|                     | 3. 3 * 9-Pin COM Port headers(COM2 Support RS422/RS485)        |
|                     | 4. 1 * IR header                                               |
|                     | 5. 1 * HDMI_SPDIF header                                       |
|                     | 6. 1 * LVDS header                                             |
| 1. BIOS             | 1. Award 4MB SPI Flash ROM                                     |
| 1. Form Factor      | 1. Mini-ITX Embedded Motherboard(170mmx170mm)                  |
| 1. Temperature      | 1. Operating within 0~60 centigrade                            |
|                     | 2. Storage within -20-85 centigrade                            |

**Product Accessories**

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- 1x IDE cable