

20.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Intel Apollo Lake-I SoC Processor (Default: E3940)
- Support 1\* SO-DIMM DDR3L-1866MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70°C
- 9~36V DC-in (Phoenix terminal connector)

|             |                                                         |
|-------------|---------------------------------------------------------|
| MB Model    | – JNF951T-E3940                                         |
| Model No.   | – HBJC386F951T-3940B<br>– HBJC386F951TW-3940B (WIFI)    |
| BIOS        | – AMI Flash ROM                                         |
| CPU/Chipset | – Intel® Apollo Lake-I SoC Processor (Default: E3940)   |
| Memory      | – 1* SO-DIMM slots DDR3L-1866MHz up to 8GB              |
| Storage     | – 1* M.2 (M-key 2280) slot for SSD                      |
| Network     | – 2* Intel i210-IT GbE<br>– 1* Full-size mini-PCIE slot |

|                 |                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>– 4* USB3.0</li> <li>– 2* RJ45</li> <li>– 1* VGA (Max. Resolution: 1920×1200@60Hz)</li> <li>– 1* HDMI (Max. Resolution: 3840×2160@30Hz)</li> <li>– 1* Line out</li> <li>– 2* WIFI Antenna (HBJC386F951TW-3940B only)</li> <li>– 1* DC-in (3 Pin Phoenix terminal)</li> </ul>                                                                  |
| Front Panel I/O | <ul style="list-style-type: none"> <li>– 1* Power SW + Power LED</li> <li>– 1* ATX &amp; AT mode Switch</li> <li>– 1* SIM Card slot</li> <li>– 2* COM (RS232/422/485_ COM1 w/power)</li> <li>– 1* Power SW (2 PIN out)</li> <li>– 1* 16 bit GPIO (8-IN, 8-OUT, Isolation Protection 2,500VDC, Output Voltage 5~20VDC)</li> <li>– 2* RS485 (Isolation Protection 2,500VDC)</li> </ul> |
| Power Source    | <ul style="list-style-type: none"> <li>– Adapter: AC 90~240V input / DC12V-5A-60W</li> <li>– MB: Support 9~36V DC-in</li> </ul>                                                                                                                                                                                                                                                      |
| Compliance      | – CE, FCC, LVD, RoHS, ErP Ready                                                                                                                                                                                                                                                                                                                                                      |
| Temperature     | <ul style="list-style-type: none"> <li>– Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD)<br/>(The test environment is closed and windless)</li> <li>– Storage Temperature: -40 ~ 80° C</li> <li>– Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>                                                                                       |
| Dimensions      | – 185 (W) x 142 (D) x 60 (H) mm                                                                                                                                                                                                                                                                                                                                                      |
| Packing         | <ul style="list-style-type: none"> <li>– Net Weight: 2.2KG</li> <li>– Gross Weight: 3.5KG</li> <li>– Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>                                                                                                                                                                                                                  |