

609.00 EUR

incl. 19% VAT, plus [shipping](#)



- Intel Comet Lake-S !
- H410 Chipset !
- 19" Enclosure !

Support:  [Datasheet](#)

- Intel® 10th LGA1200 Socket Comet Lake-S Processor (Max. 65W TDP)
- Support 2* DDR4 2666/2400MHz SO-DIMM up to 64 GB
- 3* USB3.2, 3* USB2.0, 4* COM, 1* HDMI, 1* DP, 2* RJ45, 1* MIC, 1* Line out, 1* Line in
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 250W FLEX Power

Dimensions	– 330 (W) x 192 (D) x 44 (H) mm		
MB model	– MI08-00 / Mini ITX (6.7-in * 6.7-in, 170 * 170mm) (Default) – MI08-02 (W/TPM2.0)		
Part No	Non-Wifi	Wifi	
	– HBJC150I08-H410-B	– HBJC150I08I-H410-B	
CPU/Chipset	– Intel® 10th LGA 1200 Socket Core i7/i5/i3/Pentium/Celeron Comet Lake-S Processor (Max. 65W TDP) – H410 chipset		
BIOS	– AMI 128Mb Flash ROM		
Memory	– 2* Dual CH non-ECC DDR4 2666/2400MHz SDRAM SO-DIMM up to 64GB		
Network	– 1 * Intel i219V GbE – 1 * Intel i211AT GbE		
Storage	– 2 * 2.5" or 1 * 3.5" SATA3 6Gb/s internal drive bay – 1 * M.2_SSD (M key-2242/2280) support NVMe		
Expansion	– 1* M.2 E-key 2230 (PCIex1/USB2.0) – 1* PCIex16 slot – Support onboard TPM2.0 (MI08-02) / optional		
Rear I/O Port	– 3 * USB 3.2 (Gen. 1) – 1* USB 2.0 – 1 * HDMI 1.4 (Max Resolution: 4096×2160@30Hz) – 1 * DP (Max Resolution: 4096×2304@60Hz) – 2 * RJ45 – 1 * Mic, 1 * Line in, 1 * Line-out – 4 * COM (COM 1 support RS232/422/485)		

Front I/O Port	– 1 * Power button, 1 * Reset button – 1 * Power LED, 1 * HDD LED – 2 * USB 2.0
Power Source	– 1U 250W FLEX POWER – AC 90~240V input
Certification	– CE, FCC, LVDS, RoHS
Environment	– Operating Temperature : 0°C~50°C – Storage Temperature : -10°C~70°C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Packing	– Net Weight■3.5 KG – Gross Weight■4.5 KG – Color Box Dimension■560(W) x 400(D) x 140(H) mm
Warranty	–2 Year limited warranty